

GIROPES

WEIGHING SOLUTIONS



20
years

SERIE **GI400** **repeater**

GI400_R45_13112017_V01.1_EN

GI400 R45

DESIGN

ET GIROPES FABRICATION

**QUALITY
AND MAXIMUM RELIABILITY**



GI400 R45 REPEATER

WE COUNT ON INNOVATION

VERSATILITY IN THE MOST COMPACT RANGE

MULTIPLE INDUSTRIAL APPLICATIONS

KEEP ON
DEVELOPING
NEW DEVICES

GI400 R45 repeater



- WEIGHT REPEATER
- HIGH-CONTRAST RED LED WITH 6 DIGITS OF 45 mm
- MULTIPROTOCOL
- COM1 RS232, COM2 RS232, COM3 RS485 ENTRIES
- SUM CHANNELS FUNCTION (2 by 2 or 3)
- DISPLAY WITH 3 ENTRIES (one by one)
- INCLUDED CABLE

STAINLESS STEEL

Stainless steel housing resistant according to work environment requirement.

IP65

It allows a complete protection against water dropped during its cleaning with a hose.

GENERAL SPECIFICATIONS

WORKING TEMPERATURE	-10 °C a 40 °C
SUPPORT	Mural inclinable
POSSIBLE UNITS	kg
OTHER FEATURES	Integrated clock and calendar. (to print the ticket from repeater)

SCREEN

LED FEATURES	Red LED of 7 segments with decimal. 6 digits of 45 mm high
--------------	---

SUPPLY

110-230Vac, 50/60 Hz

AVAILABLE PROTOCOLS

With the most common protocols available in the market

MORE FUNCTIONS AND OPTIONS

Giropés has developed a compact indicator with extensive functions for all types of industry, distribution, nutrition, chemical industry, chemist industry and logistics. GI400 R45, the medium size dimension repeater ideal to complete your indicator.

VERSATILE

High precision weigh indicator and repeater with compact design. Ideal for applications which require an autonomous indicator, with the possibility to include communication interfaces with connections to remote control weight repeater, PC, PLC, external or internal printer, among other possible accessories.

REPEATER OF A SINGLE INDICATOR

►0◄

►T◄

T◄

Using the equipment like a repeater of a single indicator, it allows "0" "T" setting and the tare of an GI400 indicator.

Allowing a great agility at workflow.

R
000 100



SUM CHANNELS FUNCTION

W1

W2

W3

Σ

SCHEME 1

Sum function allows, at the repeater, the function to sum up to 3 weights via the entries: COM1 | COM2 | COM3 available as standard and it shows the result on display.



W1

IN



W2

IN



W3

IN



SCHEME 2

If you do not occupy the 3 ports you can display on screen or to process by exit channel. These ports allow the possibility IN /OUT.



W1

IN



W2

IN



W3

OUT



GIROPES

www.giropes.com
 LinkedIn:giropes-sl
 giropes@giropes.com
 Pol. Empordà Internacional, C/Molló 15-16
 17469 VILAMALLA- (Girona) SPAIN
 T(34) 972 527 212 · F(34)972 527 211

SERIE

GI400
GI410i

WEIGHT-TARE + DIGITAL